



# Video Wall DSD

Open Video wall are amongst the worlds thinnest measurement and 1.8mm\*, and come in 450 nits and 700 nits, for that stunning image and can be used in a multitude of configurations.

\*Thinnest Side

DSD:	DSD46-VE
<b>Type</b>	D-LED Panel
<b>Size</b>	46"
<b>Dimension</b>	1024 x 579 x 112 mm
<b>Slim Bezel</b>	L\T : 3.5 mm R\B : 2.1 mm
<b>Weight</b>	20.5 kg
<b>Display Orientation</b>	Portrait / Landscape
<b>Mounting Options</b>	Wall
<b>Mounting Type</b>	VESA FDMI : 400x400 / 300x400
<b>Resolution</b>	1920x1080
<b>Pixel Pitch</b>	0.53x0.53
<b>Brightness</b>	450 nits
<b>Viewing Angle</b>	178/178
<b>Contrast Ratio</b>	3500:1
<b>Response Time (Average)</b>	6.5 ms
<b>Features</b>	+ Super Narrow Bezel + Video Wall Support + Auto Fan Control + RS232 Remote Control
<b>I/O Port</b>	+ AC inlet x1 / AC outlet x1 + HDMI x1 + VGA x1 + DVI x1 + Video Component x1 + Video Composite x1 + S-Video x1 + RS231 in x1 / RS232 out x1 + Audio in x2 + Speaker line out R/L
<b>AC Input / Output</b>	+ AC Input : 100~240VAC; + AC Output: 100~240VAC
<b>Power Consumption (Max.)</b>	115W
<b>Touch Screen</b>	NA
<b>Temperature</b>	+ Operating: 0° to 40° + Storage: -20° to 60°
<b>Humidity</b>	10~80% R.H. max



DSD:	DSD46-VE2
<b>Type</b>	D-LED Panel
<b>Size</b>	46"
<b>Dimension</b>	1024 x 579 x 112 mm
<b>Slim Bezel</b>	L\T : 3.5 mm R\B : 2.1 mm
<b>Weight</b>	20.5 kg
<b>Display Orientation</b>	Portrait / Landscape
<b>Mounting Options</b>	Wall
<b>Mounting Type</b>	VESA FDMI : 400x400 / 300x400
<b>Resolution</b>	1920x1080
<b>Pixel Pitch</b>	0.53x0.53
<b>Brightness</b>	700 nits
<b>Viewing Angle</b>	178/178
<b>Contrast Ratio</b>	4000:1
<b>Response Time (Average)</b>	6.5 ms
<b>Features</b>	+ Super Narrow Bezel + Video Wall Support + Auto Fan Control + RS232 Remote Control
<b>I/O Port</b>	+ AC inlet x1 / AC outlet x1 + HDMI x1 + VGA x1 + DVI x1 + Video Component x1 + Video Composite x1 + S-Video x1 + RS231 in x1 / RS232 out x1 + Audio in x2 + Speaker line out R/L
<b>AC Input / Output</b>	+ AC Input : 100~240VAC; + AC Output: 100~240VAC
<b>Power Consumption (Max.)</b>	140W
<b>Touch Screen</b>	NA
<b>Temperature</b>	+ Operating: 0° to 40° + Storage: -20° to 60°
<b>Humidity</b>	10~80% R.H. max

DSD:	DSD55-VE2
<b>Type</b>	D-LED Panel
<b>Size</b>	55"
<b>Dimension</b>	1215.2 x 686 x 87.15 mm
<b>Slim Bezel</b>	U\L : 3.4 mm D\B : 1.9 mm
<b>Weight</b>	36 kg
<b>Display Orientation</b>	Portrait / Landscape
<b>Mounting Options</b>	Wall
<b>Mounting Type</b>	VESA FDMI : 500x400 / 300x400
<b>Resolution</b>	1920x1080
<b>Pixel Pitch</b>	0.63x0.63
<b>Brightness</b>	800 nits
<b>Viewing Angle</b>	178/178
<b>Contrast Ratio</b>	1400:1
<b>Response Time (Average)</b>	10 ms
<b>Features</b>	+ Super Slim Bezel (5.3 seam) + Video Wall Matrix (up to 10x10) + OSD Support + RS232 Remote Control
<b>I/O Port</b>	+ AC inlet x1 / AC outlet x1 + HDMI x1 + VGA x1 + DVI x1 + Video Component x1 + Video Composite x1 + S-Video x1 + RS231 in x1 / RS232 out x1 + Audio in x2 + Speaker line out R/L
<b>AC Input / Output</b>	+ AC Input : 100~240VAC; + AC Output: 100~240VAC;
<b>Power Consumption (Max.)</b>	260W
<b>Touch Screen</b>	NA
<b>Temperature</b>	+ Operating: 0° to 50° + Storage: -20° to 60°
<b>Humidity</b>	90% R.H. max

Authorised Australian Distributor:  
 Goodson Imports Pty Ltd  
 142 Wicks Road  
 Macquarie Park NSW 2113  
 Offices in all main States and New Zealand  
 Ph: 02-8875 4544 Fax 02-8875 4588  
 www.goodson.com.au