

HS-2510W-2D/2512W-2D



Specification	HS-2510W-2D	HS-2512W-2D
Processor	Intel Bay Trail J1900 Quad Core CPU, up to 2.42 GHz, 2M Cache	
System Memory	DDR3L SO-DIMM x 1, max. 8GB	
Storage Device	SATA Storage x 2 (one for HDD/SSD; the other for 1" SSD only) or optional eMMC module	
Built-in Scanner	2D barcode scanner	
Power Supply	12V/60W	
OS Support	Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT/Linux per request	
Display & Touch		
LCD	9.7" TFT LCD	12" TFT LCD
Resolution	1024 x 768	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
I/O & Expansion		
Serial Port	3, DB9 x 2 + RJ50 x 1, 5V/12V support on all COM ports	
Parallel Port	Yes	
Standard USB Port	4, USB 3.0 x 1 + USB 2.0 x 3	
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support for Posiflex monitors	
CR Port	1, control 2 CR via optional Y-cable	
PS/2 Port	Yes	
Audio	Line-out x 1	
Expansion Slot	Mini-PCIe slot x 1	
Physical Dimension		
Dimension (W x D x H in mm)	224.5 x 185 x 387	297 x 187 x 402
Weight (N. W. in kg)	4.2	5.3
Environmental		
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
Built-in Options		
MSR	3 tracks ISO or JISII (HID/VCOM selection)	
FPU	Optical type	
WiFi	Mini-PCIe WiFi/BT module	
RFID Reader	Support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)	
Smart Card Reader	Yes	



Taking Space Saving to Extremes

HS-2510W-2D/2512W-2D

Space Saving All-in-one POS Terminal

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice.

* Please refer to the website for more attachment options.

Certifications



EN2017 12V2



POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan

Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw

Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller

HS-2510W-2D/2512W-2D

POSIFLEX

The **HS-2500-2D Series** is the solution for the counter space problem. It takes the all-in-one concept to the extremes! It comes with the 2D barcode scanner in place of the built-in thermal printer. The compact all-in-one design of HS-2500-2D Series frees more room for counter space, so that the store owner can display and promote more merchandizes to maximize sales opportunities.



Compact

The compact footprint of HS-2500W-2D Series makes itself adaptable to a wide range of counter styles and allows every inch of the work space usage to be optimized, thus creating maximum profit return for the store owners. This is what space saving is all about.

Innovative All-in-one Terminal

As an "all-in-one" solution, the HS-2500W-2D Series touch screen terminal integrates some of the most widely used peripherals in daily POS operation, such as barcode scanner, MSR, smart card reader, fingerprint sensor and 2nd customer display, and has the features and functionality to cater for applications in retail, hospitality, health care, banking and more, while offering uncompromising performance.



Aesthetics

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, the HS-2500W-2D Series is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.



2D Barcode Scanner



Optional Built-in MSR,
Smart Card Reader,
Fingerprint Sensor
and RFID Reader