

Specialized Solution!

2 inch Barcode Label Printer

SLP-DX220



Coffee & Tea Shop



Retail



Healthcare & Pharmacy



Post & Parcel



Peeler



Standard



Auto-cutter

Advanced Performance

- Printing speed up to 6 ips (152 mm/s)
- Fast data processing speed of various types of label

Smart Media Detection™

- Automatic paper detection such as gap media, black mark media and short length media paper



BIXOLON®

2 inch Barcode Label Printer

SLP-DX220

a Better Solution for your Business™



Standard

Peeler

Auto-cutter

FEATURES

Dual interface

- Standard: Serial + USB
- Optional: Ethernet + WLAN* + USB




User-friendly Design

- Easy paper loading with adjustable paper guide
- Pause and cancel function-keys



Powerful Compatibility

The SLP-DX220 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



BPL-Z™

BPL-E™

Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-DX220-EN-JUL13

Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

SPECIFICATIONS

Printer Specifications

Print Method: Direct Thermal
Print Speed: SLP-DX220: Up to 6 ips (152 mm/s) / SLP-DX223: Up to 4 ips (100 mm/s)
Print Resolution: SLP-DX220: 203 dpi / SLP-DX223: 300 dpi
Print Width: SLP-DX220: Up to 54 mm / SLP-DX223: Up to 56.9 mm
Print Length: 6 ~ 2000 mm
Media Sensor: Transmissive, Reflective (adjustable), Head open

Media Characteristics

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width: 15 ~ 60 mm
Media Roll Diameter: Up to 130 mm
Media Thickness: 0.06 ~ 0.20 mm
Supply Method: Easy Paper Loading

Physical Characteristics

Dimensions (WxLxH): 120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)
Weight: 1.36 kg (2.99 lbs.)
Power: EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory: 64MB SDRAM, 128MB Flash
Interface: Dual Interface
 Standard: Serial+USB V2.0 HS
 Optional: Ethernet+WLAN*+USB V2.0 HS
 * WLAN: 802.11b/g/n USB dongle type (optional)

Environment Characteristics

Temperature: Operating: 0 ~ 40°C (32 ~ 104°F)
 Storage: -20 ~ 60°C (-4 ~ 140°F)
Humidity: Operating: 10 ~ 80% RH
 Storage 10 ~ 90% RH

Software

Emulation: SLCS, BPL-Z™, BPL-E™
Driver/Utility: Windows Driver (Euro Plus/Seagull), OPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB / Ethernet Driver, Utility Program, Label Artist™
SDK: Android SDK

Fonts / Graphics / Symbolologies

Character Sets:

- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Bitmap Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbolologies:

1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock)

BIXOLON®
 www.bixolon.com



BIXOLON Co., Ltd.

7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

Authorised Australian Distributor:

Goodson Imports Pty Ltd

142 Wicks Road

North Ryde NSW 2113

Offices in all main States and New Zealand

Ph: 02-8875 4544 Fax 02-8875 4588

www.goodson.com.au