ThinkVision T24m MONITOR

PRODUCTIVITY AND VERSATILITY. DISPLAY OF EXCEPTIONAL VALUE.



PROFESSIONAL PERFORMANCE WITH AFFORDABLE USB TYPE-C.

There's no need to compromise performance and functionality for price. The affordable ThinkVision T24m-10 has it all - 23.8" of Full-HD Near-Edgeless display for outstanding images and crisp text from center to sides, along with convenient One-Cable solution USB Type-C and broad connectivity. It is ideal for enterprise and home, office, also features full-function, ergonomic stand and TüV eye comfort certification to optimize your use experience.

WHY YOU SHOULD BUY THE THINKVISION T24m-10 MONITOR



Truly Superior Display

The brilliant 23.8" Full-HD (1920 x 1080) wide-view display features In-Plane Switching for clear, vivid imagery, and response time as low as 4 ms to minimize motion blur.



Convenient One-cable Connection

A single USB Type-C cable delivers video and power to a notebook, tablet or smartphone, along with versatile digital ports make device connectivity easy.




Ergonomic Design

Suits any environment with full-function adjustable stand.

THE THINKVISION T24m-10 MONITOR IS BEST SUITED FOR



Businesses that need full, wide-screen monitors that can fit in limited deskspace.





IT managers seeking a versatile, affordably-priced monitor suitable for mass deployment.





ThinkVision T24m-10 MONITOR

23.8"

WLED

16:9

Yes

1920 x 1080

250 cd/m²

72% NTSC

178°/178°

1000:1

3M:1

92

19 W

116 W

<0.5 W

<0.5 W

Internal

90 VAC - 264 VAC

47 Hz - 63 Hz

In-Plane Switching

527.04 (H) x 296.46 (V)

0.2745 (H) x 0.2745 (V)

4 ms (Extreme mode) 6 ms (Normal mode)

SPECIFICATIONS

DISPLAY

Panel Size Panel Type Backlight Resolution Aspect Ratio Anti-Glare Screen Dimensions (W x H) (mm) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio (Typical) Pixel Pitch (mm) Dot/Pixel Per Inch (DPI/PPI) Color Gamut (CIE 1931) Response Time (gray to gray)

POWER CONSUMPTION

Typical Maximum Sleep-Mode Switch Off-Mode Power Supply Power Voltage Voltage Dynamic Frequency

CONNECTIVITY

Video Input Signals

Video Cables Supplied Video Cable Length USB Hub

HDMI 1.4 + DisplayPort 1.2a + USB Type-C USB Type-C to Type-C Cable 1.8 m Yes 1 x USB 3.01 (Upstream, by USB Type-C) 4 x USB 3.01 (Downstream, incl. 1BC) Yes (3.5 mm)

Audio-Out

MECHANICAL

Tilt Angle (Front / Back) Swivel Angle (Left / Right) Lift Range (mm) Pivot VESA Mount (mm x mm) Kensington Lock Slot Cable Management Bezel Color Bezel Width Top (mm / inches) Sides (mm / inches)

-5° / 30° +/-45° 110 +/-90° Yes (100 x 100) Yes Yes Raven Black 2 / 0.08" 2 / 0.08"

DIMENSIONS (W x D x H)

Size Packed	
(mm)	422 x 622 x 190
(inches)	16.61" x 24.48" x 7.48"
Size Unpacked with Stand	
Lowest Position	
(mm)	540.2 x 261.75 x 373.4
(inches)	21.26" x 10.3" x 14.7"
Highest Position	
(mm)	540.2 x 261.75 x 483.4
(inches)	21.26" x 10.3" x 19"
Size Unpacked without Stand	
(Monitor Head Only)	
(mm)	540.2 x 46.45 x 325.98
(inches)	21.26" x 1.82" x 12.83"
Distance from Table to Panel	
Lowest Pixel at Bottom of Screen	
(mm / inches)	70.37 / 2.77"
Highest Pixel at Top of Screen	
(mm / inches)	476.8 / 18.77"
Stand Base Footprint Area	
(mm / inches)	250 x 250 / 9.84" x 9.84"
Weight	
Packed	Starting at 16.39 lbs (7.45
Unpacked	Starting at 11.33 lbs (5.15 k
Monitor Head Only	Starting at 7.26 lbs (3.3 kg
Full Container Load	1140 / 540 Units
(40' STD / 20' STD)	

SPECIAL FEATURES

Thin Client Support (Tiny)

WHAT'S IN THE BOX

Monitor with Stand 1 x Power Cable 1 x USB Type-C[™] to Type-C[™] Cable Quick Setup Guide

CERTIFICATIONS

EPEAT ENERGY STAR Rating ULE TCO RoHS (EU 2002/95/EC) Windows Certification China Energy Efficiency Standard TüV Eye Comfort Certification

Silver 8.0 Gold TCO 7.0 / TCO Edge 2.0 Vac Windows 7 / Windows 10 Tier 2 Yes

16.39 lbs (7.45 kg)

11.33 lbs (5.15 kg)

7.26 lbs (3.3 kg)

(by Tiny Clamp Bracket Kit + VESA Mount)

Yes

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for Lenovo reserves the right to alter product ofterings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible tor any editorics. Frademarks: The following are trademarks or registered trademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or registered trademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or ensure trademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or registered trademarks or ensure trademarks ore ensure tradema