



Self-Service
Customer Engagement

Stellar TK-2100 Series

21.5" Modular Kiosk



HIGHLIGHTS

- 21.5" true-flat PCAP touch screen
- Flexible configurations: floor-standing, countertop
- Expandable pedestal for extra functionalities:
bill acceptance, card dispensing, ticketing and
pager dispensing
- Modular design for easy serviceability
- Reversible printing direction
- Ideally for self-service applications in retail, food-service,
hospitality, healthcare, ticketing



Windows/Android



NFC/RFID reader



2D scanner



Fingerprint sensor



Status Indicator



EMV Supportive*



Versatile Functionality

PT-200BC



Floor-standing
with Card Dispenser & Bill Acceptor

PT-300



Floor-standing
with Ticket Printer



Countertop

PT-200



Floor-standing

PT-500



Floor-standing
with Pager Dispenser

PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-200



- Thermal Printer
- Reserved space for Customized bracket for EMV payment devices
- 2D Scanner



- Status Indicator
- Camera
- Proximity Sensor
- NFC/RFID Reader
- MSR / Fingerprint Sensor

PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-200BC



PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-300



PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-500



Specifications		TK-2111	TK-2130	TK-2150	
Computer	Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz	Intel Bay Trail J1900 Quad Core, up to 2.42 GHz, 2M Cache	Intel Kaby Lake U Core i3/i5/i7	
	System Memory	DDR4 4 GB	DDR3L SO-DIMM slot x 1, max 8 GB	DDR4 SO-DIMM slot x 2, max 32 GB	
	Storage Device	32 GB eMMC + microSD slot x 1		SATA SSD x 1	
	Intel vPro Support	N/A	N/A	Core i3: N/A Core i5/Core i7: Optional	
	TPM Support	N/A		Optional	
	Power Supply	12V/84W x 1 + 24V/60W x 1		12V/60W x1 + 24V/60W x1	
	OS Support	Android 9.0*/Android 10.0 with GMS	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT	Windows 10 IoT 64 bit	
	Serial Port	RJ50 x 2, 5V/12V support on all COM ports		6, DB9 x 1 + RJ50 x 5, 5V/12V support on all COM ports	
	Standard USB Port	6, USB 3.0 x 1 + USB 2.0 x 5	6, USB 3.0 x 1 + USB 2.0 x 5	6, USB 3.0 x 2 + USB 2.0 x 4	
	OTG USB	Micro-USB x 1		N/A	
	Display Port	HDMI x 1		MiniDP x 1	
	LAN Port	10/100 Mb x 1, 10/100/1000 Mb x 1		10/100/1000 Mb x 1	
Audio	Internal 3W speaker x 2		Internal 3W speaker x 2		
Internal Expansion Slot	N/A		M.2 x 1		
Display & Touch	LCD		21.5"		
	Resolution		1920 x 1080		
	Touch		True-flat PCAP touch with multi-touch support		
Physical Dimension	Dimension (W x D x H in mm)		Countertop version: 400 x 460 x 832 Floorstanding version: 625 x 610 x 1620		
	Weight (N. W. in kg)		Countertop version: 27.5 Floorstanding version: 60		
Environmental	Operating Condition	0°C - 50°C, 20%RH - 90%RH	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)		
	Storage Condition		-20°C - 70°C, 10%RH - 90%RH		
Standard Components	Status Indicator		RGB Color LED Indicator		
	Proximity Sensor		Range from 60 cm to 100 cm		
	Camera		1MP wide angle camera		
	Printer		3" thermal printer w/auto cutter, 200 mm/sec (max.)		
Optional Components	WiFi	USB dongle	M.2 WiFi/BT module		
	Scanner		2D barcode scanner		
	EMV Payment Device Bracket Support*		Custom bracket support for various EMV payment devices		
	MSR		3 tracks ISO or JISII (HID/VCOM selection)		
	Fingerprint Sensor		Optical type		
	NFC/RFID Reader		Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18092)		
	Optional Items for Pedestal PT-200BC				
	Bill Acceptor		Storing up to 900 notes		
	Card Dispenser		Integrated RFID Reader/Writer, supporting ISO 14443 Type A/B contactless cards; Storing up to 262 cards		
	Optional Item for Pedestal PT-300				
	Ticket Printer		Fanfolded ticket printer for ticket thickness: .004" to .011", ticket width: 2.0" to 3.25"		
	Default Items for Pedestal PT-500 (UPCOMING)				
	Pager Dispenser	Capacity		Storing up to 40 pager units	
		Speed		2.5 sec per pager	
Pager/Receiver	Frequency		430-460MHz		
	Dimension (Diameter x H in mm)		100 x 100 x 16.5		
	Weight (N. W. in g.)		96		
Transmitter	Frequency		440-460MHz		
	Power Supply		5V/2A adapter		
	Dimension (W x D x H in mm)		180 x 120 x 30		
	Weight (N. W. in g.)		475		

Note: Bill Acceptor & Card Dispenser can be set in the same pedestal PT-200BC, but only the pedestal PT-300 can accommodate Ticket Printer while pedestal PT-500 can only accommodate Pager Dispenser. *Google Play services is not supported by this device. *Designed and Manufactured in Taiwan by Posiflex Technology, Inc. *Posiflex does not sell the EMV payment devices, but can provide bracket support with an additional charge. *The product information and specifications are subject to change without prior notice.