



TX-5000/5000E

Powerful Fan-free POS Box

TX-5000 Series is the latest high-end fan-free POS Box. Incorporating leading CPU technology - 4th generation Intel® Haswell processor, TX-5000 Series provides unmatched performance while juggling multiple programs with ease.

TX-5000/5000E

High Performance

With SSD and the 4th generation Intel Haswell processor up to Core i7, TX-5000 Series is faster, cooler and more efficient. In conjunction with patented fan-free technology, it delivers the unparalleled performance at completely silent operation.

Compact and Hassle-free

Small footprint design allows this POS box to be placed anywhere you need a Point of Service system. Built-in PoweredUSB ports free up the need for multiple power adapters for peripherals and keep the counter neat and tidy.

Expandable and Flexible

Connect to a wide range of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

System Configuration	TX-5000	TX-5000E
Processor	Intel G1820/2.7GHz/2M Cache Intel G3320TE/2.3GHz/3M Cache Intel Core i3-4330TE/2.4GHz/4M Cache Intel Core i5-4570TE/2.7GHz up to 3.3GHz/4M Cache Intel Core i7-4770TE/2.3GHz up to 3.3GHz/8M Cache	
System Memory	DDR3 1333 SO-DIMM x 2, max. 16GB (DDR3 1333/1600 for Core i3 and above CPU)	
Storage Device	SATA Storage x 2, factory default 32GB SSD x 1	
RAID	N/A	
Power Supply	12V/80W	12V/150W
OS support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Linux per request	
Connectivity Serial Port	6 DR9 v 4 COM5 / COM6 via antional cable from	service window 5V/12V support on all COM ports
Parallel Port	6, DB9 x 4, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports 1	
Standard USB Port	8 (USB 3.0/2.0 x 2 + USB2.0 x 6)	5 (USB 3.0/2.0 x 2 + USB 2.0 x 3)
PoweredUSB Port	N/A	24V x 1 + 12V x 2
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support for Posiflex monitors; DP x 1	
CR Port	1, control 2 CR via optional Y-cable	
PS/2 Port	N/A	
UPS Port	N/A	
Audio	Internal 2W speaker x 1 (optional) + Mic-in/Line-out	
Internal Expansion Slot	mini-PCle slot x 1	
Built-in Device		
Built-in WIFI	Optional mini-PCle WIFI module	
Physical Dimension		
Dimension (W x D x H in mm)	220 x 202 x 83	
Weight (N. W. in kg)	2.75	
Environmental		
Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	

Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.



Authorized Distributor / Reseller

2015Q1