

Zepto POS



Cable Management Design



Die-cast Casing



VESA Mount Capable*

* Mounting poles/brackets not included.

SENIOR



SPECIFICATIONS

	Zepto POS 6400	Zepto POS 6500
PROCESSOR	Intel Celeron J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Core i5-6360U 2.0 GHz (Turbo Boost up to 3.1 GHz)
SYSTEM MEMORY	4 GB DDR4 RAM (up to 32 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE	1 x M.2 SATA and PCIe SSD	1 x M.2 SATA and PCIe SSD

DISPLAY

SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels
BRIGHTNESS	300 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	4 x USB 3.0, 2 x USB 2.0
SERIAL PORT	3 x RJ48
VIDEO PORT	1 x HDMI
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (DC 12 V / 24 V) controlled by GPIO port

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro
---------	-----------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	355 (W) x 303 (H) x 200 (D) mm 4.6 kg	
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	75 x 75 mm	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 55°C	
HUMIDITY	Operating: 20% to 80% Storage: 20% to 85% (non-condensing)	
POWER CONSUMPTION	12 V / 5 A, external power adapter, 100-240 V, 50/60 Hz	12 V / 7.5 A, external power adapter, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR
CUSTOMER DISPLAY	10" TFT LCD display or 2-line VFD

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.