

rSPOS



Stainless Steel
SUS 304 Chassis



Waterproof Circular Connectors



IP66 Certification
Fanless & Ventless

SEÑOR



SPECIFICATIONS

	rSPOS 970 (17") rSPOS 9220 (21.5")	rSPOS X370 (17") rSPOS X3220 (21.5")
PROCESSOR	Intel Quad Core Celeron J1900 2.0 GHz (Turbo Boost up to 2.42 GHz)	Intel Dual Core i3-6100U 2.3 GHz
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE	64 GB half-slim SATA SSD	64 GB half-slim SATA SSD

DISPLAY

	17" TFT LCD 21.5" TFT LCD	17" TFT LCD 21.5" TFT LCD
SIZE	17" TFT LCD 21.5" TFT LCD	17" TFT LCD 21.5" TFT LCD
RESOLUTION	1280 x 1024 pixels 1920 x 1080 pixels	1280 x 1024 pixels 1920 x 1080 pixels
BRIGHTNESS	350 cd/m ² 250 cd/m ²	350 cd/m ² 250 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (10 point, multi-touch)	Projected capacitive touch (10 point, multi-touch)

I/O INTERFACE

USB PORT	Up to 3 x USB 2.0	Up to 3 x USB 2.0
SERIAL PORT	1 x DB9	1 x DB9
ETHERNET PORT	Up to 2 x RJ45 10/100/1000 Mbps	Up to 2 x RJ45 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	POSReady 7 / Windows 7 Pro / 10 IoT / 10 Pro
---------	--

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	17": 408 (W) x 337 (H) x 84 (D) mm 7.6 kg 21.5": 535 (W) x 326 (H) x 84 (D) mm 9.6 kg
CHASSIS MATERIAL	SUS 304 stainless steel
VESA PATTERN	75 x 75 mm / 100 x 100 mm
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C Customized: -10°C to 50°C
HUMIDITY	10% to 90% (non-condensing)
POWER CONSUMPTION	DC output: 12 V / 6 A 72 W (max.) AC input: 100 V-240 V

MODEL OPTIONS

WIRELESS LAN	Wi-Fi 802.11 b/g/n
CUSTOMISED I/O PORTS	3 x USB & 1 x LAN 2 x USB & 2 x LAN

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.