

x3POS



VESA Mount



Wall Mount



IP54 Whole Unit

SENOR



SPECIFICATIONS

x3 J64

x3C X35

PROCESSOR	Intel Celeron Quad Core J6412 1.5 GHz (Turbo Boost up to 2.6 GHz)	Intel Core i3-7020U 2.3 GHz
SYSTEM MEMORY	4 GB DDR4 RAM	4 GB DDR4 RAM
STORAGE DEVICE	1 x removable M.2 PCIe SSD / 1 x removable M.2 SATA SSD	

DISPLAY

SIZE / RESOLUTION	11.6" TFT LCD (LED backlight) / Full HD 1920 x 1080 pixels
BRIGHTNESS	300 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	5 x USB 2.0, 1 x USB 3.0 (side)
SERIAL PORT	2 x RJ50
AUDIO PORT	2 x built-in speakers / 2 x 2 W
CASH DRAWER	1 x RJ12 (24 V)
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	10 IoT (64-bit) / 10 Pro (64-bit)
LINUX	Kernel 3.0 up

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	285 (W) x 44~376 (H) x 195 (D) mm 4.5 kg	
CHASSIS MATERIAL	Aluminium die-cast & Polycarbonate-ABS	
IP RATING	IP54 whole unit	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	10% to 90% (non-condensing)	
POWER CONSUMPTION	19 V / 3.15 A, external power adaptor, 100-240 V, 50/60 Hz	19 V / 6.31 A, external power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED READERS	3-track MSR, Fingerprint reader, RFID, 2D image reader
CUSTOMER DISPLAY	11.6" FHD LCD or 2-line VFD
WIRELESS LAN	Integrated Dual Band Wi-Fi 802.11 b/g/n/ac (2x2 MIMO) + Bluetooth 4.1
COLOURS	Dark Grey (standard) White (optional)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.