

### Overview

#### Epson TM-m30II POS Receipt Printer



### Models

Epson TM-m30II POS Receipt Printer	340U1AA
Epson TM-m30II POS Receipt Printer White	340U2AA
Epson TM-m30II POS Receipt Printer Japan	38N27AA
Epson TM-m30II POS Receipt Printer White Japan	38N28AA

### Introduction

The Epson TM-m30II POS Receipt Printer is a compact receipt printer with multiple interface options.

### Key Benefits

- Sleek 3" thermal receipt printer; compact footprint; ideal for counter spaces
- Interface options: USB, Ethernet
- Print speeds up to 250 mm/sec
- 150 km printhead life and auto cutter life of 1.5 million cuts<sup>1</sup>
- Reduce paper usage by up to 30 percent<sup>2</sup>
- Three-year limited warranty from HP

<sup>1</sup> Epson's statements about reliability levels are only estimates based on normal use of the printer using tested media only. See

### Overview

[www.epson.com/testedmedia](http://www.epson.com/testedmedia) for more information on Tested Media. These reliability statements are not warranties of the media or Epson's printers, and the only warranties for printers are the limited warranty statements for each printer.

<sup>2</sup> Paper savings depend on the text and graphics printed on the receipt.

---

### Compatibility

The Epson TM-m30II POS Receipt Printer is compatible with the HP Point of Sale Systems.

**NOTE:** Not all Point of Sale system models are available in all regions.

---

### Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

### Technical Specifications

#### General

<b>Fonts</b>	Font A: 12 x 24 48 cpl (default); Font B: 10 x 24 57 cpl; Font C: 9 x 17 64 cpl
<b>Character Set</b>	95 Alphanumeric, 18 International, 128 x 43 Graphic (including user-defined page); Standard firmware includes Traditional/Simplified Chinese, Thai and Korean; requires utility to set the desired language support. The Japan-specific models will support Japanese.
<b>Two-dimensional Symbol Printing</b>	PDF417, MaxiCode, DataMatrix, Aztec Code, Two-dimensional GS1 DataBar, Composite Symbology
<b>Data Buffer</b>	Receive Buffer: 4KB or 45byte NV Bit Image Memory 12KB (max) NV graphics: 384KB (max)
<b>Receipt-Columns Paper Roll Size</b>	Type: Thermal roll paper Paper Feed Method: Friction feed Width: 3.12"/79.5 mm Paper Loading: Drop-in Roll Diameter (Max): 3.27"/83 mm Core Diameter (Min): 0.71"/18 mm Paper Guide: Yes
<b>Knife</b>	Auto Cutter
<b>Resolution</b>	203 dpi
<b>Cash Drawer Kick</b>	Yes
<b>LED Indicators</b>	Orange LEDs – Error, Paper Out; Blue LEDs – Power, Ethernet
<b>Barcodes</b>	UPC-A, UPC-E, JAN8 / EAN8, JAN13 / EAN13, Code39, Code93, Code128, ITF, CODABAR(NW-7), GS1-128, GS1 DataBar, Code 128 Auto
<b>Print method</b>	Thermal line printing
<b>Print speed</b>	250 mm/second
<b>Mechanical</b>	<b>Dimensions (WxDxH)</b> 5" x 5" x 5" 127 x 127 x 135 mm

### Technical Specifications

	<b>Weight</b>	2.87 lb/ 1,300 g
	<b>Color</b>	ENB9 (Epson White), EBCK (Epson Black)
<b>Interface/Connection</b>	<b>Interface</b>	Built-in USB-Type-B (USB 2.0, Full-speed) + Ethernet 10/100Base-T/TX
<b>Power</b>	<b>Consumption</b>	Operating 32.4 W Standby 1.0 W (AC115 V/60 Hz)
<b>Temperature Range</b>	<b>Operating</b>	5 to 45°C (41 to 113°F) at 10 to 90% Humidity
<b>Drivers</b>	Epson Advanced Printer Driver (APD), TM Virtual Port Driver, Mac Printer Driver, CUPS Driver	
<b>Development Kit</b>	Epson ePOSTM SDK (iOS, Android, JavaScript), TM Print Assistant (iOS, Android), OPOS ADK/OPOS ADK for .NET (Windows), JavaPOS ADK (Windows, Linux)	
<b>Other Tools</b>	Deployment Tool, Monitoring Tool, TM-m30II Firmware Updater	
<b>Software</b>	TM Utility (iOS, Android), TM-m30II Utility (Windows Desktop), EpsonNet Config (Win, Mac), TM Bluetooth Connector, Deployment Tool, Monitoring Tool	
<b>Operating System Compatibility</b>	iOS®, Android™, Windows®, GNU (Linux)	
<b>Reliability</b>	17 million printing lines MTBF 360,000 hours MCBF 65,000,000 lines Auto Cutter Reliability: 1.5 million cuts	
<b>Agency Certifications</b>	EMI FCC Class A, ICES-003 Class A, Safety Standard UL62368-1/CSA C22.2 No.62368-1 ENERGY STAR® qualified RoHS compliant	
<b>Box contents</b>	TM-m30II, Power Supply - Adapter C1, Power Switch Cover, Roll Paper (for checking initial movement of the printer), Setup Guide, 58 mm Roll Paper Guide. Cables sold separately.	
<b>Cables (sold separately)</b>	Recommended cables: 1 C5A0AA - Epson 6-ft USB Cable OR 2LR29AA - Epson 10-ft USB Cable  Alternate configurations: 2KH40AA - Epson 10-ft Powered USB Y Cable (no power supply required)	

### Summary of Changes

Date of change:	Version History:		Description of change:
	From v1 to v2		

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies.