



Epson TM-T82IVL

Next generation cost effective POS printer

- Designed for businesses with a low volume of POS transactions
- All-in-one box with accessories
- Ease-of-use features
- Ease-of-maintenance features
- Paper saving function
- Epson quality and reliability

Epson TM-T82IVL



All-in-one-box convenience

For TM-T82IVL, all the accessories are included in the box for quick setup and installation. The box includes quick setup guide, paper roll, AC cable, USB cable (for USB-Serial model).

Fast printing with multiple options

The TM-T82IVL prints both text and graphics on receipts at speeds up to 250 mm/sec. It also features crisp, clear printing of logos, coupons and barcodes. In addition, the TM-T82IVL offers paper saving options that can reduce paper usage by up to 30%.

Reliability you can count on

The TM-T82IVL is the ideal choice for retailers with a low volume of POS transactions but who require fast print speed with enhanced reliability. Based on Epson's advanced printing technology, the TM-T82IVL delivers the quality and reliability that Epson is known for, which ensures an easy, reliable printing solution for end users.

With an MCBF of 60 million lines, and an auto cutter life of 1.5 million cuts, the TM-T82IVL delivers best-in-class reliability that you can count on in your daily operation.

Retail hardened features

Internal printer mechanisms are housed in a rigid sheet-metal chassis for extra protection.

Easy to use. Easy to maintain.

The TM-T82IVL comes with multiple ease-of-use features from drop-in paper loading, partial-cut auto-cutter to status LEDs. The printer has a built-in power adapter, eliminating the need for an external power adapter. The internal printer mechanisms and circuitries are also designed for easy replacement and maintenance, reducing the cost of repair and repair time.

Product Specifications

PRINT SPECIFICATIONS

| | |
|-------------------------------------|---|
| Product name | TM-T82IVL |
| Print method | Line thermal |
| Dot density | 203 dpi x 203 dpi |
| Print speed | Max. 250 mm/s |
| Print width (80 mm paper width) | 72 mm±0.5 mm |
| Fonts | 12x24 (Font A), 9x17 (Font B) |
| Column capacity (80 mm paper width) | 48 (Font A), 64 (Font B) |
| Character size | 1.25x3 mm (Font A), 0.88x2.13 mm (Font B) |
| Character set | Alphanumeric 95, International character 18 set, Graphics 128x43 page |
| Characters | ANK |
| Barcode | UPC-A, UPC-E, JAN8/EAN 8, JAN13/EAN13, Code39, Code93, Code128, ITF, CODABAR(NW-7), GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1DataBar Expanded |
| 2-dimensional symbols | PDF417, QR code, Maxi Code, Two-dimensional GS1 DataBar, Composite Symbology |
| Paper size (80 mm paper width) | 79.5±0.5 mm |
| Diameter | 83 mm |
| Paper thickness | 53-75 µm |
| Auto cutter | Partial cut (one point in center left uncut) |
| Sensors | Roll paper end, Cover open |
| MCBF | 60 million lines |
| MTBF | 360,000 hours |
| Auto cutter life | 1.5 million cuts |
| Head life | 100 km, 15 million lines |
| Interface | USB 2.0+RS-232C; Ethernet |
| AC adapter | Embedded |
| Power source | AC100~240V, 50~60Hz |
| Stand-by | Approx. 0.4 W |
| Receipt printing | Approx. 27.8 W |
| Temperature | Operation 5-45°C / Storage - 10-50°C |
| Humidity | Operation 10-90% / Storage - 10-90% |
| Noise level | Approx. 55 dB (bystander position) |
| Overall dimensions | 140 mm (W) x 192 mm (D) x 137 mm (H) |
| Weight | Approx. 1.5 kg |
| Color | EBCK |
| Installation | Horizontally |
| Operating systems | Windows, MacOSX, iOS, Android, Linux |
| Data buffer | Selectable as 45 bytes or 4 KB |
| What's in the box | Thermal roll paper, User's manual, AC cable, USB cable (USB+Serial Model only) |
| Options / accessories | External buzzer OT-BZ20 |
| Ordering information | TM-T82IVL - 841 USB+Serial, (Product Code : C31CL45841) TM-T82IVL - 842 USB+Ethernet (Product Code : C31CL45842) |

Better Products for a Better Future

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA
Level 7, 90 Arthur
Street, North Sydney
NSW 2060 Tel: 1300
361 054
www.epson.com.au

EPSON NEW ZEALAND
Level 2 7-9 Fanshawe Street
Auckland, 1010
Tel: 0800 237 766
www.epson.co.nz

Epson CoverPlus

Fast. Reliable. Professional

EPSON